

SPINDLE SERVO MOTOR

<http://www.szghauto.com>



Spindle Motor Model	Rated Power (KW)	Rated Torque (Nm)	Rated Current(A)	Max Speed (RPM)	Rated Speed (RPM)	Matched Driver
SZGH08-3-9.5-1.5/2.2-4-1500	1.5	9.5	3.7	8000	1500	SZGH-S4T1P5
SZGH08-4-14-2.2/3.7-4-1500	2.2	14	6	8000	1500	SZGH-S4T2P2
SZGH09-2-24-3.7/5.5-4-1500	3.7	24	9.5	8000	1500	SZGH-S4T3P7
SZGH10-2-35-5.5/7.5-4-1500	5.5	35	13	8000	1500	SZGH-S4T5P5
SZGH10-3-48-7.5/11-4-1500	7.5	48	17	8000	1500	SZGH-S4T7P5
SZGH10-4-71-11/15-4-1500	11	71	23.5	8000	1500	SZGH-S4T011
SZGH13-2-95-15/18.5-4-1500	15	95	31	8000	1500	SZGH-S4T015
SZGH13-3-117-18.5/22-4-1500	18	117	38	8000	1500	SZGH-S4T018
SZGH13-4-140-22/30-4-1500	22	140	45	8000	1500	SZGH-S4T022
SZGH16-1-191-30/37-4-1500	30	191	60	6000	1500	SZGH-S4T030
SZGH16-2-235-37/45-4-1500	37	235	75	6000	1500	SZGH-S4T037
SZGH16-3-286-45/55-4-1500	45	286	90	6000	1500	SZGH-S4T045
SZGH16-4-350-55/75-4-1500	55	350	110	6000	1500	SZGH-S4T055
SZGH18-1-478-75/90-4-1500	75	478	148	4500	1500	SZGH-S4T075
SZGH18-2-573-90/110-4-1500	90	573	176	4500	1500	SZGH-S4T090
SZGH18-3-700-110/132-4-1500	110	700	210	4500	1500	SZGH-S4T110
SZGH22-1-840-132/160-4-1500	132	840	255	4000	1500	SZGH-S4T132

SPINDLE SERVO DRIVER

<http://www.szghauto.com>



Spindle driver Model	Matched Motor's Power(KW)	Rated Output Current(A)	Rated Output Capacity(KVA)	Min Brake Resistor(Ω)	Cable Diameter(mm ²)
SZGH-S4T1P5	1.5	3.5	2.5	0.5kw/75 Ω	2.5
SZGH-S4T2P2	2.2	5	3.8	0.5kw/75 Ω	2.5
SZGH-S4T3P7	3.7	8	5.6	1kw/40 Ω	4
SZGH-S4T5P5	5.5	13	8.6	1kw/40 Ω	6
SZGH-S4T7P5	7.5	17	11	1.5kw/32 Ω	6
SZGH-S4T011	11	25	17	1.5kw/26 Ω	6
SZGH-S4T015	15	32	20	1.5kw/26 Ω	10
SZGH-S4T018	18	39	26	2kw/40 Ω *2	10
SZGH-S4T022	22	45	30	2kw/40 Ω *2	16
SZGH-S4T030	30	60	40	2.5kw/40 Ω *3	25
SZGH-S4T037	37	75	50	2.5kw/40 Ω *3	25
SZGH-S4T045	45	90	60	2.5kw/40 Ω *4	35
SZGH-S4T055	55	110	72	2.5kw/40 Ω *4	50
SZGH-S4T075	75	150	99	2.5kw/40 Ω *6	70
SZGH-S4T090	90	178	99	2.5kw/40 Ω *8	70
SZGH-S4T110	110	210	145	2.5kw/40 Ω *9	90
SZGH-S4T132	132	255	145	2.5kw/40 Ω *10	90